

ADDENDUM #1

To drawings and specifications for

SOUTHWEST SANITARY SEWER REHABILITATION

for the City of Sidney

This Addendum must be acknowledged on the Proposal Form

To All Contractors:

This Addendum modifies the Original Drawings, Bid Document and Specifications and is to be taken into account in preparing proposals and will become part of the Contract Documents:

Legal Notice

Amend first paragraph from:

The City of Sidney is accepting sealed bids ... until 11:30 a.m. (EST) on Thursday, December 1, 2016 at which time all bids received will be publicly opened and read aloud. The non-refundable cost of the packet is \$20.00.

to:

The City of Sidney is accepting sealed bids ... until **11:30 a.m. (EST) on Thursday, December 8, 2016** at which time all bids received will be publicly opened and read aloud. The non-refundable cost of the packet is \$20.00.

Notice to Contractors

Amend first paragraph from:

Sealed proposals, properly endorsed, for the furnishing of all necessary labor until 11:30 a.m. (EST) on Thursday, December 1, 2016 and at that time publicly opened and read.

to:

Sealed proposals, properly endorsed, for the furnishing of all necessary labor Until **11:30 a.m. (EST) on Thursday, December 8, 2016** and at that time publicly opened and read.

Instructions to Bidders, Page 3

Amend third paragraph from:

Bidders are invited to be present at the opening of the proposals, which will occur at the City Municipal Building, 201 W. Poplar Street, Sidney, Ohio at 11:30 A.M. (EST) on Thursday, December 1, 2016.

to:

Bidders are invited to be present at the opening of the proposals, which will occur at the City Municipal Building, 201 W. Poplar Street, Sidney, Ohio at **11:30 a.m. (EST) on Thursday, December 8, 2016.**

Bid Forms

Page 6

Amend:

Item 9, Special, Lining of Manholes (protection from Hydrogen Sulfide) 21-23 feet deep, 3 each

To:

Item 9, Special, Lining of Manholes (protection from Hydrogen Sulfide) 21-23 feet deep, **2 each**

Amend:

Item 16, Special, Cured In Place lining of 21-inch VCP Sanitary Sewer, 3147 LF

To:

Item 16, Special, Cured In Place lining of 21-inch VCP Sanitary Sewer, **2562 LF**

Add:

Item 10, Special, Lining of Manholes (protection from Hydrogen Sulfide) 21-22 feet deep excluding lining of invert and by-pass pumping

Renumber items accordingly.

Supplemental Specifications

Add the following notes and/or conditions to page 77:

- Any and all contractors or subcontractors entering upon Cargill Corporation owned property must abide by their regulations which include but may not be limited to safety training, testing and safety procedures as established by Cargill.
- The first sanitary manhole on the north side of the CSX Railroad mainline tracks shall be lined from the new manhole casting to the invert bench and excludes the flow channel of the manhole. No by-pass pumping will be performed for this manhole due to the inability to pump

across the railroad tracks.

- Due to the inability to by-pass pump sewage across the railroad spur line track and the railroad main line tracks the sections of pipe between manholes that cross beneath the tracks is being eliminated from pipe lining bids.
- Due to the inability to by-pass pump sewage across the railroad spur line track and the railroad main line tracks the sections of pipe between manholes that cross beneath the tracks must be pressure grouted with live flows.
- All access routes to the sanitary sewer and manholes in the field south of the railroad main line tracks must follow directly over or immediately adjacent to the sanitary sewer path. Any materials used (gravel or matting) to stabilize access for equipment must be removed upon completion of work. Any fences disturbed must be replaced as quickly as possible in area(s) where livestock are present and temporary gates may be required per the needs of the land owner.

FOR REFERENCE ONLY
NOT FOR BID SUBMITTAL